Test point for super-small panel

This type is convenient for signal line check on a panel and for taking out of signal. Using together with a M3 nut, it is very compact in size and easy to use.

For signal line check

Part No.: **PN-1-1-C, PN-1-2-C** (10pcs/pack)

- This is used for checking the signal line.
- Material Pin part: Brass

Resin part (main body): 9T nylon (UL94V-0)

Nut: Brass, Nickel plating


- Finish Pin part: Gold plating over nickel base
- Resin color: BLACK, RED, YELLOW, GREEN, BLUE, WHITE
- Adaptive panel thickness: 0.5mm to 5.0mm
- Panel fitting hole diameter: φ 3.2


■ How to order



• See the next page for specifications and precautions for use.







For oscilloscope

Part No.: PN-2-1-C (10pcs/pack)

- This type is easy for rooking the oscilloscope probe.
- Material Pin part: Brass

Resin part (main body): 9T nylon (UL94V-0)

Nut: Brass, Nickel plating

- Finish Pin part: Gold plating over nickel base
- Resin color: BLACK, RED, YELLOW, GREEN, BLUE, WHITE
- Adaptive panel thickness: 0.5mm to 5.0mm
- Panel fitting hole diameter: φ 3.2

■ How to order



- See the next page for specifications and precautions for use.
- To avoid touching the metal part. PN-6-1 is available.



