Male pin for HH-1

Part No.: **HJ-1** (100pcs/pack)

- This male pin is for the connector for surface mounting (HH series).
- By crimping electric wire to this product and mounting it to HH series, signal can be taken out from the board for surface mounting.
- There is no problem even if the pin contacts with the pin nearby, as long as the shrinkage tube for HJ-1 (HJ-T) is being used.
- Material: Brass
- Finish: Gold plating over nickel base
- Electric wire diameter that can be fit: Thinner than AWG26

• Rated current: 2A

■ Part No.: HJ-1

• Recommended crimping tool:

Part No.: OMXT-1

• Edge chip for OMXT-1: Part No.: X-7

Please purchase both products




Shrinkage tube for HJ-1

Part No.: **HJ-T** (100pcs/pack)

- This is a shrinkage shrinkage tube for HJ-1.
- Please shrink the tube by applying heat with a dryer after fitting it to HJ-1.
- Material: Silicone rubber
- Color: Gray
- Operating temperature range: -50 to +150℃

■ Part No.: HJ-T







Metal lock for HH-1


Part No.: HH-1-R (100pcs/pack)


- This product is a metal lock used to prevent the male pin (HJ-1) being taken off easily from the connector for surface mounting. (HH-1 series)
- Please use this in a place with vibration and for increasing reliability.
- Please use this when HH-1 is horizontally mounted.
- Material: Beryllium copper
- Finish: Nickel plating





How to use the metal lock (HH-1-R)





Example of usage

