


Fitting mount without hole for printed board


SF, SG series (100pcs/pack)

- This is used for fixing by insertion when there is no space for drilling a fitting hole to a PC board such as surface mounting board and high-density mounting board.
- For a large PC board, please insert SG series to the side.
- The distance between a chassis (base) and a PC board is 1.5 mm. If a longer distance is required, any distance (mm) can be set by inserting EP series underneath to raise them.
- Material: Acetal copolymer milky white (UL94HB)
- Operating temperature range: - 40 to + 85°C





Part No.

Part No.	A	B	Printed board thickness
SF-0.6	0.55	1.95	0.6
SF-0.8	0.75	1.75	0.8
SF-1.0	0.95	1.55	1.0
SF-1.2	1.15	1.35	1.2
SF-1.6	1.55	0.95	1.6



SF series


Example of usage



When EP series is used for SF series


Part No.

Part No.	A	B	Printed board thickness
SG-0.6	0.55	1.95	0.6
SG-0.8	0.75	1.75	0.8
SG-1.0	0.95	1.55	1.0
SG-1.2	1.15	1.35	1.2
SG-1.6	1.55	0.95	1.6



SG series

Fitting hole position



•Please insert EP series underneath to raise 1.5 mm or over from the chassis (base).

