# Resin type

### Spacer of round shape for printed board

## **BP, 4BP series** (100pcs/pack)


- This is used for fitting a printed board to a chassis, and other adaptive cases.
- Material: Acetal copolymer (UL94HB)
- Color: BLACK
- Operating temperature range: 40 to + 85  $\ensuremath{^\circ}$



#### ■ For M3 screw


Part No.	А	L
BP-5	Through hole	5
BP-7.5	Through hole	7.5
BP-10	Through hole 10	
BP-12.5	Through hole 12.5	
BP-15	6 or over 15	
BP-17.5	6 or over 17.5	
BP-20	6 or over 20	
BP-25	6 or over 25	
BP-30	6 or over	30





Part No.	L	
4BP-4	4	
4BP-5	5	
4BP-6	6	
4BP-7	7	
4BP-8	8	
4BP-9	9	
4BP-10	10	
4BP-11	11	
4BP-12	12	
4BP-13	13	
4BP-14	14	
4BP-15	15	
4BP-16	16	
4BP-17	17	
4BP-18	18	
4BP-19	19	
4BP-20	20	
4BP-25	25	
4BP-30	30	

■ For M4 screw



# Spacer of hexagon shape for printed board CQ series (100pcs/pack)

- The whole part of this spacer is resin.
- Material: Special polyamide resin (UL94HB)
- Color: BLACK
- $\bullet$  Operating temperature range: 40 to + 125  $\ensuremath{\mathbb{C}}$
- Tightening torque: 2.5kgf-cm or less

#### Part No.

Part No.	L
CQ-8	8
CQ-10	10
CQ-15	15
CQ-20	20



