




Power supply connector for surface mounting

HH-3 series

- This connector is used for supplying power to a surface mounting board.
- The male side is HJ-3 and HJ-31.
- By using HH-3-R (metal lock fitting) for HJ-2, it will not be taken off even if it is pulled.
- Two types (a type with magazine and a type with embossed tape) are available.
- Material
 - Body: Brass
 - Contact part: Beryllium copper
- Finish
 - HH-3-G: Body: Gold plating over nickel base
 - HH-3-S: Body: Contact part: Gold plating over nickel base
Body: Tin plating over nickel base
Contact part: Gold plating over nickel base




■ Example of usage



When HJ-3 and HH-3-R (metal lock fitting) are used

■ Recommended land information



- Specification
 - Rated current: 5A
 - Contact resistance: 10m Ω or less
 - insertion / removal durability : 100 cycles
 - Insertion forces: 150g or over
 - Removal forces: 150g or over
 - Adaptive male pin diameter: φ 0.8 to φ 1.0
 - Operating temperature range: - 40 to + 125°C

■ Part No.

Part No.	Package
HH-3-G	Magazine (100pcs/pack)
HH-3-G-T	Reel (500pcs/reel)
HH-3-S	Magazine (100pcs/pack)
HH-3-S-T	Reel (500pcs/reel)

■ Instructions for use

- Please be careful of the direction for inserting the pin.
The groove side is the direction for inserting the male pin.

